

VEINED AFRICA

The Veined collection consists of pure quartz, structural polyester resin and UV-stabilised colour pigments. The Veined Africa surface has a uniform black background, a fine grain and widespread white veins.



Format Standard

305 cm x 140 cm (4.27 sqm)
120" x 55" (45.96 sqft)

Thicknesses | Weights*

1.2 cm x 1/2" | 125 kg - 275 lb
2 cm x 3/4" | 208 kg - 459 lb
3 cm x 1 1/4" | 312 kg - 688 lb

Finish

polished, matt

* The indicated weight can vary by about 5% due to the different weight specific for the various classes of product.

Category: 2

Apparent density EN 14617-1:2013	kg/cm ³	2368	W3 (EN 15285:2008)
Water absorption EN 14617-1:2013	%	0,04 - 0,07	W3
Flexural strenght EN 14617-1:2016	Mpa	70.1	F4 (EN 15285:2008)
Compressive strenght EN 14617-15:2006	Mpa	232	
Impact resistance EN 14617-9:2005	J	9.2	
Linear thermal expansion EN 14617-11:2005	10 ⁻⁶ °C ⁻¹	37.7	
Chemical resistance (HCl and NaOH) EN 14617-10:2012	Classe	C4 for hydrochloric acid C4 for sodium hydroxide	
Abrasion resistance EN 14617-:2012	mm	29.6	A3 (EN 15285:2008)
Slip resistance by means of the pendulum tester (polished finish) EN 14231-:2003		SRVdry= 47 SRVwet= 4	

Certifications



Quartzforms SpA

Burger Str. 10 D-39126 Magdeburg, tel +49 (0) 39 1 53 888 000, fax +49 (0) 39 1 53 888 010
info@quartzforms.com www.quartzforms.com

Colours and brightness of video and printed reproductions are indicative.

The slab simulates natural stone so, some changes are possible in the final product.

900

VEINED AFRICA



Colours and brightness of video and printed reproductions are indicative. The slab simulates natural stone so, some changes are possible in the final product.